A Dissertation

On

Beyond Visualization: Integrating 3D Fashion Technology into Virtual Prototyping, Embellishment Placement, and Apparel Product Development

A Practice-Based Study of CLO3D, Digital Material Realism and Production Workflow Optimization in Bangladesh

Submitted by: Shafiqul Islam

ID: 2201401011

Batch: 23rd

Major in Fashion Design

Supervised by: Engr. Md. Sadiqur Rahman

Lecturer

Department of Fashion Design & Technology

Uttara University, Dhaka, Bangladesh

Submission date: 12 November 2026

Letter of Transmittal

12 November 2026

To

Engr. Md. Sadiqur Rahman

Lecturer

Department of Fashion Design & Technology

Uttara University, Dhaka, Bangladesh

Subject: Submission of Dissertation on 3D Fashion Technology in Apparel Product Development

Dear Sir,

I am submitting my dissertation entitled “Beyond Visualization: Integrating 3D Fashion Technology into Virtual Prototyping, Embellishment Placement, and Apparel Product Development.” The study draws on my work in fashion design and 3D development at Al-Muslim Group and examines virtual sampling, size-graded embellishment templates, digital plotting, realistic denim materials and workflow automation. It follows the seven-chapter academic structure from introduction and literature review through methodology, practical case analysis, findings and recommendations. I respectfully submit the report for your review.

The report follows the academic chapter sequence of introduction, literature review, theory, methodology, analysis, findings and recommendations. I would be grateful for your review and guidance.

Sincerely,

Shafiqul Islam

2201401011

Declaration of Originality

I, Shafiqul Islam (Student ID: 2201401011), declare that this dissertation is submitted as part of my Bachelor of Science in Fashion Design at Uttara University. The practical accounts are based on my professional experience; secondary research is attributed in the references. Illustrative workflows are distinguished from independently verified measurements, and no survey or experimental data have been fabricated. I take responsibility for reviewing the final manuscript, its factual accuracy, originality and compliance with university and workplace disclosure requirements.

Signature: _____ Date: _____

Certification of Supervision

This dissertation has been submitted for review under the academic supervision of the undersigned. Certification is valid only following the supervisor's examination and signature.

Supervisor name: Engr. Md. Sadiqur Rahman
Designation: Lecturer
Department: Fashion Design & Technology
Uttara University, Dhaka, Bangladesh

Supervisor signature: _____

Acknowledgment

I express my sincere gratitude to the faculty of the Department of Fashion Design & Technology at Uttara University for their academic guidance. I also acknowledge the professional experience gained at Al-Muslim Group, where I have worked in fashion design and digital development since August 2025 and currently lead a four-member 3D design team. Practical collaboration with pattern, CAD, merchandising, embroidery, print and sample departments has shaped the issues examined in this study. I thank colleagues whose technical questions encouraged me to improve digital workflows. No confidential customer artwork, correspondence or proprietary production file is reproduced without permission.

Abstract

Three-dimensional (3D) fashion technology is increasingly used to develop and communicate garments before physical sampling. This practice-based dissertation investigates the industrial role of CLO3D beyond garment rendering through three connected areas: virtual garment prototyping, graded embellishment placement, and workflow optimization. The study draws on the author's professional experience in the 3D design function of a Bangladesh apparel manufacturer, including childrenswear template preparation for a UK buyer and virtual jeans development for an international buyer. The first case documents how a size-6 reference is translated into age-graded placements for embroidery, print and crochet; revised through buyer comment workbooks; and transferred to physical patterns. A practitioner-developed digital output route CLO3D PDF to Illustrator SVG to Inkscape HPGL, followed by compatible marker/plotter software is analyzed against a manual print-cut-stick method. The second case traces DXF pattern import, simulation on buyer-matched avatars, rendering, review comments and virtual corrections before physical sampling. Additional analysis concerns denim wash texture creation, physically informed fabric behavior, and small AutoHotkey automations used in repetitive CLO3D tasks. Methodologically, the dissertation is a descriptive, qualitative study using retrospective professional observation, process mapping and literature-supported technical interpretation. Results are presented as observed workflow capabilities and limitations, not as statistically measured cost or time savings. The study concludes that effective 3D adoption depends on dimensional verification, material calibration, clear revision records and robust handoffs between digital design and production. It proposes practical controls and future measurements to assess efficiency, accuracy and reduction of unnecessary physical samples.

Keywords: CLO3D; virtual prototyping; apparel product development; embellishment placement; garment grading; digital sampling; Bangladesh; pattern CAD.

Table of Contents

Letter of Transmittal **2**
Declaration of Originality **3**
Certification of Supervision **4**
Acknowledgment **5**
Abstract **6**
Table of Contents **7**
List of Tables and Figures **9**
Chapter 1: Introduction **10**
1.1 Background of the Study 10
1.2 Rationale of the Study 11
1.3 Problem Statement 12
1.4 Research Questions 12
1.5 Research Objectives 13
1.5.1 Main Research Objective 13
1.5.2 Specific Objectives 13
1.6 Significance of the Study 13
Chapter 2: Literature Review **15**
2.1 Development of 3D Virtual Prototyping in Fashion 15
2.2 Traditional and Digital Product Development 15
2.3 CLO3D, Pattern CAD and Interoperability 16
2.4 Digital Fabrics and Visual Realism 17
2.5 Virtual Fit and Physical Fit 18
2.6 Industrial Applications in Bangladesh 18
2.7 Literature Gap 19
Chapter 3: Theoretical Discussion **20**
3.1 Theoretical Framework 20
3.1.1 Digital Product Development Concept 20
3.1.2 Complementary Technical Concepts 21
3.1.3 Integration of Concepts 21
3.2 Conceptual Framework 21
3.3 Evaluation Questions and Indicators 22
Chapter 4: Research Methodology **23**
4.1 Research Design 23
4.2 Case Selection and Scope 23
4.3 Data Collection 24
4.4 Research Instruments and Software 24
4.5 Quality Control and Validation 25
4.6 Analysis Techniques 25
4.7 Ethical Considerations 26
4.8 Expected Findings 26
4.9 Limitations 26
Chapter 5: Data Presentation and Analysis **28**
5.1 Case A: Childrenswear Graded Embellishment Templates 28
5.2 Provisional Artwork Scale Matrix 29
5.3 Template Approval Sequence 29
5.4 Digital-to-Physical Handoff 30
5.5 Case B: Buyer-Led Virtual Prototyping 31

5.6 Comparative Workflow and Evidence Status 32
5.7 Revision and Comparison Log 33
5.8 Analysis of Technical Constraints 33
5.9 Case C: Denim Wash Visualization and Digital Material Realism 34
5.10 Workflow Micro-Automation Using AutoHotkey 34
5.11 Practical Performance Indicators 35
5.12 Synthesis and Evidence Boundaries 36
Chapter 6: Findings and Practical Design Development 37
6.1 Preliminary Findings of the Case Analysis 37
6.1.1 Two Practical Roles of CLO3D 37
6.1.2 Buyer Comments Drive Iterative Development 37
6.1.3 Manual Handoffs Remain Important 37
6.1.4 Fit Realism Has Practical Limits 37
6.1.5 Direct Plotting Addresses a Post-Approval Bottleneck 37
6.1.6 Detailed Denim Rendering Supports Visual Communication 38
6.1.7 Reusable Assets and Micro-Automation Support Repetitive Work 38
6.1.8 An Integrated Digital Workflow Is Not Yet a Sample-Free Workflow 38
6.2 Design Translation and Original Demonstrator Development 38
6.2.1 Design Concept 38
6.2.2 Material and Surface Development 39
6.2.3 Garment Lineup and Technical Specifications 39
6.2.4 Virtual Fit and Final Render Presentation 40
Chapter 7: Recommendations and Conclusions 41
7.1 Recommendations 41
7.2 Conclusion 42
References 21

List of Tables and Figures

Table 3.1: Conceptual dimensions and proposed evaluation criteria 22
Table 5.1: Initial artwork scale bands for the working example.....29
Table 5.2: Comparison of workflow stages and evidence status 32
Table 5.3: Illustrative buyer-comment and revision log.....33
Table 5.4: Proposed performance indicators and evidence limitations 35
Table 6.1: Original demonstrator lineup and technical evidence 39
Figure 3.1: Three-track conceptual framework of applied 3D development.....21
Figure 5.1: Digital artwork-to-plotter conversion and verification 31
Figure 5.2: Buyer-led 3D review process before physical sampling.....32

Chapter 1: Introduction

1.1 Background of the Study

Fashion design and apparel product development involve a sequence of linked activities including design interpretation, pattern making, size grading, prototype development, fit assessment, buyer review and production communication. In a conventional development process, physical samples and printed templates may carry a substantial part of the design information between departments. Three-dimensional garment software creates opportunities to evaluate a garment digitally before manufacture, but its value depends on how accurately digital information can be communicated to the rest of the production workflow.

CLO3D is used to construct and simulate garments from two-dimensional patterns. The software can also support the import of DXF apparel patterns from industrial CAD systems (CLO Virtual Fashion, n.d.). During my work in fashion design and development at Al-Muslim Group, two distinct CLO3D functions have become important: virtual sampling for design and fit review, and the development of scaled embellishment-placement templates for garments manufactured in several sizes. These functions involve different deliverables, different forms of buyer review and different downstream departments.

In the childrenswear workflow, the design team receives or develops a garment template at a reference size. Digital patterns and artwork are aligned through the CLO3D 2D workspace using graphic placement and internal lines, and the motif's relative size and location are assessed across graded sizes. Screenshots and placement measurements are reviewed by a local technical team and subsequently by the international buyer team. Once approved, a physical pattern and printed motif are used by production departments. In the virtual sampling workflow, DXF patterns are imported into CLO3D, assembled on a buyer-specified avatar and adjusted after visual buyer feedback. Physical sampling follows the accepted 3D stage, as instructed by the buyer.

The author has developed 3D fashion skills through self-directed study since approximately 2022–2023 and later applied them professionally. Since August 2025 he has been involved in fashion design and development at Al-Muslim Group, a denim-oriented manufacturing organization. He currently coordinates 3D development with four team members. The scope of his work includes buyer-facing virtual samples and production-facing technical templates, as well as collaboration with departments responsible for pattern making, samples and surface embellishments. This involvement offers an insider perspective, although it also requires explicit recognition of possible researcher bias.

The term “3D fashion design” in this study therefore refers to a connected process rather than a single image-making operation. The process can begin with pattern data, progress through fabric simulation and visual review, and end with updated design instructions or physical pattern output. The output may be a persuasive visual render, a digitally revised pattern, an embellishment-placement document or a plotted production template. Each form has a different quality requirement.

1.2 Rationale of the Study

Literature has documented both the possibilities and limitations of virtual garment fitting. Lee and Park (2017) found differences between virtual and physical assessment at garment regions including necklines, sleeves and shoulders. More recent work in the Bangladesh-ready-made garment context reviews the potential value of 3D sampling while also identifying training, material representation and implementation challenges (Baria et al., 2026). These studies justify examining digital development as a process that must be integrated with physical sampling and existing industrial systems, rather than treating simulation alone as a complete substitute for manufacture.

A practical research opportunity arises where placement approvals are represented by screenshots and measurements, yet later departments require full-scale artwork on physical patterns. The transition between digital visual review and physical plotter output may require printing, cutting, manually positioning and rescanning an artwork motif. This dissertation documents that handoff and evaluates what a more reliable, scale-controlled digital transfer would require. It does not presume that a particular software conversion has been successfully validated.

This subject is relevant to Bangladesh because export garment development depends on fast communication across buyers, designers, technical teams and factories. Product decisions frequently cross national borders. Reducing unnecessary physical iterations may help teams respond faster to feedback, but a rendering alone cannot eliminate the need to test production fabric, finishing and real fit. A study grounded in actual workflows can identify where digital tools help and where a physical control remains essential.

In addition, apparently minor actions repeating a menu command, entering the same simulation thickness, retrieving a saved seam effect or repositioning several motifs can accumulate into substantial routine work. The author’s development of small workflow automations and reusable assets invites examination of productivity as a socio-technical issue: software capability, user skill, correct process design and departmental coordination all matter.

1.3 Problem Statement

The adoption of 3D apparel software does not automatically create a continuous digital production workflow. In the studied professional setting, virtual samples can support buyer-facing decisions before physical samples, but approved embellishment templates still pass through manual operations before embroidery or print production. This can create additional handling stages and potential risks of placement error, artwork scaling error, loss of visual information or inconsistency between the approved digital view and the physical template. Meanwhile, 3D fit approvals rely on the fidelity of the avatar, the fabric representation and the interpreted buyer comments. There is a need to document these workflows systematically and determine where CLO3D provides practical value, where manual steps remain necessary and what evidence would support claims of improvement.

The central problem is discontinuity between approved digital intent and production execution. For a multi-size childrenswear style containing several embroidery, print or crochet motifs, manual reproduction of artwork on graded patterns requires separate printing, cutting, alignment and attachment. The author reports that preparing a complete set of physical templates for approximately fourteen sizes can occupy at least a working day, depending on complexity. This is a retrospective estimate and is not treated as independently timed evidence.

Another problem concerns interpretation of virtual garments. A highly realistic denim image may communicate a proposed wash effectively but may not reproduce exactly what will emerge from chemical and mechanical washing. Likewise, an avatar with the same nominal measurements as a physical mannequin makes virtual review more consistent, but does not guarantee equivalent fabric tension, compressibility or final fit. The dissertation treats these differences as validation questions rather than assuming digital accuracy.

1.4 Research Questions

1. How is CLO3D used for both virtual garment prototyping and graded embellishment-placement development in an industrial apparel setting?
2. How is buyer feedback translated into revised patterns, virtual samples and size-specific motif templates?
3. Where do manual and digital process handoffs occur, and what operational limitations do they introduce?
4. Which observable measures could be used to evaluate development time, iterations, scale consistency and visual fit decisions?

5. How can a practical design and production workflow be improved without compromising buyer specifications or garment accuracy?

1.5 Research Objectives

1.5.1 Main Research Objective

To investigate the practical integration of CLO3D into apparel product development through two industrial workflows virtual prototyping and graded embellishment placement and to evaluate opportunities for clearer, more efficient digital-to-physical communication.

1.5.2 Specific Objectives

6. Document the base-size to graded-size digital template process for embroidery, print and crochet placement.
7. Describe the buyer-review cycle from an initial 3D garment simulation to physical sample authorization.
8. Identify manual transfer tasks between CLO3D, industrial pattern CAD, plotting and embellishment production.
9. Develop a transparent case-study evidence framework using approved screenshots, measurements, version histories and observation logs.
10. Propose a practical improvement framework and identify what must be tested before its benefits can be claimed.

An additional objective is to document an implemented, practitioner-developed route for exporting approved artwork and pattern outlines to a plotter via PDF, SVG and HPGL, including the controls needed to keep dimensions correct. A further objective is to explain how fabric physical properties, denim wash maps, layered surface details and micro-automation affect the usefulness and speed of virtual sampling.

The study does not test a causal hypothesis with a questionnaire. Instead, it uses guiding evaluation propositions: digital review can move selected corrections earlier; controlled artwork plotting can reduce manual placement stages; and reusable assets and automation can reduce routine user actions. Each proposition is assessed at the level of process explanation, with measurable claims explicitly deferred where records are unavailable.

1.6 Significance of the Study

The dissertation contributes a practice-focused description of two uses of 3D apparel technology that are often discussed separately. For design students, it shows how three-dimensional visualization is connected to graded templates, CAD patterns and commercial

approval processes. For designers and technicians, it identifies handoffs where information quality may be lost. For apparel manufacturers, it offers a transparent way to measure workflow performance without treating unverified time or cost reductions as facts. The scope is intentionally limited to the documented experience and evidence available to the researcher rather than broad statistical generalization.

The expected contribution is a reusable set of technical procedures: a buyer-comment-to-template revision sequence, a dimensionally controlled PDF–SVG–HPGL transfer checklist, a virtual fit review procedure, and a catalog of rendering and automation practices. These procedures may be informative for other fashion graduates and development teams, but they are not asserted to be universally valid across software versions and machine models.

Chapter 2: Literature Review

2.1 Development of 3D Virtual Prototyping in Fashion

Three-dimensional apparel prototyping connects conventional pattern engineering with virtual garment assembly, fabric simulation and digital visualization. Rather than beginning with a physical toile, a designer can import or generate pattern pieces, define sewing relationships, place a garment on an avatar and inspect its appearance digitally. Papachristou, Kalaitzi and Pissas (2023) present a methodological framework for integrating virtual prototyping into design development, illustrating how 3D practices can become part of a broader development method rather than an isolated image-production activity.

Virtual prototyping must be distinguished from the narrower task of photorealistic visualization. A render portrays the appearance of a design under selected lighting, material and camera settings. A virtual prototype connects 2D pattern geometry to simulated seams, size, avatar shape and material response. A production-ready digital package additionally needs controlled measurements, version identification, technical annotations and export compatibility. Confusing these levels of digital maturity can result in visually approved images that are difficult to reproduce on the factory floor.

Papachristou, Kalaitzi and Pissas (2023) discuss a methodological framework linking virtual prototyping to specific garment development operations. Their work provides a relevant conceptual precedent: a digital model becomes more valuable when its information can be used at later stages of making. This dissertation applies a comparable process emphasis to embellishment templates and denim sample review, without claiming to replicate their experimental procedures.

2.2 Traditional and Digital Product Development

The practical distinction between digital and conventional processes is not binary. A workflow may include digital pattern data, virtual review, physical output, manual assembly and later production scanning. The relevant research question is therefore not simply whether a process is “digital,” but which task requires which representation. Virtual visualization helps stakeholders discuss proportions and design features before material commitments, while plotted full-size patterns and motif placements may remain essential when production departments work with physical templates. The sequence and integrity of these handoffs should be evaluated case by case.

In a conventional sample route, a tech pack informs the first pattern and a physical sample is sewn, washed if relevant, checked internally, dispatched to a buyer and revised following

comments. Each physical correction may involve renewed pattern editing, sample sewing and shipping. A 3D-assisted route moves selected silhouette, pocket, proportion and visible design decisions into an earlier digital review. However, production trials and actual material tests remain necessary where dimensional accuracy, treatment effects and durability are concerned.

This suggests that the benefit should be evaluated per category of change. Pocket size or visual placement may be comparatively easy to judge on a consistent 3D view, while the final hand-feel, distressing, laundering effect and real-world garment movement may require physical inspection. Therefore, reducing sample count is a plausible objective, not a finding of this dissertation.

2.3 CLO3D, Pattern CAD and Interoperability

Pattern interoperability is central to digital apparel workflows. The official CLO documentation describes DXF import and export capabilities for apparel CAD data, including DXF-AAMA and DXF-ASTM formats; scale, grading and line-import options require attention (CLO Virtual Fashion, n.d.). The existence of DXF export does not by itself establish that a graphics-enabled template will be accepted as a production-ready file in every target plotter or Lectra installation. File-format support, graphic representation, scale fidelity and hardware interpretation must each be checked in a representative test case.

The official CLO guidance documents both DXF pattern interchange and AI/PDF export options (CLO Virtual Fashion). These capabilities establish a basis for multi-application workflows, but they do not guarantee that every object will transfer. In particular, it matters whether an element remains a vector path, becomes a raster graphic, or is flattened into a representation that another system cannot interpret. Scale and origin should be checked at every transition.

The author’s practical route uses CLO3D pattern PDF output, Adobe Illustrator conversion to SVG, and Inkscape HPGL output before sending the file to compatible marker/plotter software. Inkscape maintains an HPGL output extension (Inkscape Project, n.d.). The presence of export features should not be confused with verified accuracy on a specific industrial plotter: plotting units, origin, pen settings, strokes, path conversion and actual measured output still require validation.

A further distinction exists between HPGL as a plotting language and pattern CAD formats such as proprietary marker or model files. Converting a PDF to HPGL can give usable plotter geometry where supported, but it does not reconstruct garment pattern metadata, seam rules, grading or the original industrial CAD project. Consequently the process is evaluated as a

plotting and template-communication solution, not as a full substitute for Lectra Modaris pattern engineering.

2.4 Digital Fabrics and Visual Realism

The simulated appearance of a garment depends on the relationship among pattern geometry, sewing constraints, the virtual avatar and fabric parameters. Surface texture maps may add visual information such as weave, embossing or printed effects, while physically simulated fabric behavior requires appropriate fabric settings. A normal map can produce a lighting-based surface appearance, whereas a height map describes relative surface height for a compatible material workflow; these should not be treated as proof that real fabric drape or construction is reproduced. Accurate representation calls for comparison with actual fabric or a physical sample when available.

Digital realism has at least two different components. Geometric or physical realism concerns how the cloth drapes, stretches and reacts to contact and gravity. Surface realism concerns its color, pattern, finish, roughness, stitch appearance and rendered lighting. A beautiful wash texture can visually improve denim without correcting an inaccurate bending parameter. Conversely, realistic drape can look unconvincing if the shading, seam detail or wash appearance is weak. The two must be developed together.

For physically informed simulation, fabric measurements may include weight, thickness, stretching response and bending behavior. The CLO Fabric Kit documentation describes measuring fabric weight, thickness, bending and stretch before entering values into the software (CLO Virtual Fashion, n.d.-c). In practical terms, warp/weft orientation and shear response also affect folds and bias movement. These parameters should be documented rather than guessed when accurate virtual fitting is the objective.

Texture maps perform separate functions. A color/albedo map describes visible color including denim wash zones; a roughness map affects light scattering; a normal map changes the apparent direction of microscopic surface detail without directly changing mesh topology; a height map describes elevation information that may be interpreted by bump/displacement systems depending on the application. In practice, Photoshop can be used to prepare jeans wash images, while Substance 3D Painter can support more complex layered seam and puckering effects. A higher-resolution map cannot compensate for fundamentally wrong pattern geometry or poorly calibrated fabric behavior.

On denim, localized fading, whiskers, abrasion and different washed zones should align to the garment’s construction and body geometry. Distortion around side seams and darts can reveal

a poorly prepared texture. The author prepares wash images in Photoshop, applies the resulting artwork/textures in CLO3D, then evaluates overall appearance from consistent camera viewpoints. Additional surface treatments are sometimes authored in Substance 3D Painter when layered seam puckering or surface complexity is difficult to achieve in a single CLO effect.

2.5 Virtual Fit and Physical Fit

Lee and Park (2017) compared virtual and physical garments and identified both useful similarities and discrepancies in specific fit areas. Porterfield and Lamar (2017) analyzed the collaborative process of virtual fittings, including communication of fit issues and design changes. These studies support the use of virtual prototyping to inform decisions while cautioning against equating a convincing rendered image with validated physical fit. The present research therefore distinguishes a buyer's visual acceptance of a render from a measured confirmation of garment fit after sampling.

Lee and Park (2017) found that virtual and physical garment evaluations may agree for some measures yet differ around specific fit locations and phenomena, including shoulder slope, neckline, gapping and puckering. Porterfield and Lamar (2017) further examine how virtual fitting affects communication and collaboration between a garment maker and a designer. These findings support a balanced position: virtual fitting can be useful for review and iteration, but its quality depends on how the model is prepared and how participants interpret what they see.

A buyer-specified virtual avatar and corresponding physical mannequin can improve the consistency of comparisons when their measurements are aligned. Nevertheless, nominal measurement matching is only a starting condition. Physical body compressibility, gravity behavior, real fabric hysteresis, wash shrinkage and sewing variation may still create differences. A practical validation must compare agreed garment measurements and visible fit criteria between the simulated garment and a real sample after its intended finishing.

2.6 Industrial Applications in Bangladesh

Baria and colleagues (2026), in a review focused on 3D sampling in the ready-made garment industry, discuss the opportunities for digital sampling in relation to efficiency, resource use and product development, together with constraints such as technical training and realistic material representation. The Bangladesh context makes interoperability, department coordination and approval procedures relevant research concerns. A small, practice-led case

study can describe these concerns in operational terms, even when a large-sample numerical evaluation is not feasible.

The review by Baria and colleagues (2026) specifically considers 3D sampling in the ready-made garment industry and discusses potential advantages in efficiency, material waste and product lead time, alongside barriers including investment, training and inadequate material realism. Their review provides a context for the present Bangladesh-based case description. It does not, by itself, establish that a particular factory or practitioner achieved a specific percentage of savings.

In the described workplace, 3D output is not restricted to the rendering team. It also influences CAD, physical plotter output, sample making and the departments handling embroidery or prints. This cross-department role helps explain why file-format compatibility and documentation quality can be as important as the visual result.

2.7 Literature Gap

Research commonly evaluates virtual garment appearance, fit and sampling opportunities. This dissertation focuses additionally on graded embellishment templates: the design must preserve a buyer-approved motif composition while the garment dimensions and motif scale may change across age sizes. A further contribution is documenting how these templates move from digital buyer review to manual plotting, cutting, attachment and scanning. The claimed gap is specific to the combined operational focus of this dissertation; it is not a claim that no prior study exists on 3D design or embellishment placement.

An additional gap concerns operator-created micro-automation. Academic discussions of apparel digitization often emphasize large software investments; this case also considers automation of repetitive user interactions and reuse of frequently needed render settings. These practices are not substitutes for reliable software engineering, but they can affect the amount of time spent performing small operations during a normal development day.

Chapter 3: Theoretical Discussion

3.1 Theoretical Framework

The theoretical basis is a socio-technical process perspective on apparel development. Technical tools do not act independently: results arise from the interactions of software functions, skilled operators, established review procedures, buyer requirements and manufacturing output channels. The study also uses an input–process–output view to trace changes in the representation of a garment and its embellishments as information moves between departments. Neither framework is used here to claim causal effects unsupported by measured data.

A socio-technical approach considers the joint action of people, software, files, standards and machines. In this study a buyer's approval applies to design intent, but that intent can be altered in the transition from a simulated pattern to a screenshot, from a screenshot to a printed motif, or from a vector file to the plotter. Each stage therefore requires both a technical transfer method and a responsible person who verifies it.

The author uses a process-centered analytical framework rather than adopting the consumer-response S-O-R model used in the reference dissertation. This avoids forcing an unrelated psychological theory onto a technical apparel development problem. The guiding dimensions are visualization fidelity, dimensional fidelity, review-cycle traceability, handoff quality and operator efficiency.

3.1.1 Digital Product Development Concept

A digital apparel workflow links pattern geometry, virtual appearance, design instructions, grading and production communication. Each representation may contain different information. For example, an image can demonstrate how a motif looks on a garment but may not serve as a full-scale cutting or plotter instruction. A DXF pattern can encode pattern geometry but may not automatically preserve the full graphics used for approval. The study distinguishes visual fidelity, dimensional fidelity and process compatibility.

Digital continuity refers to maintaining the identity and validity of product information as it travels between software and departments. A pattern version, an artwork version and a buyer-approved scaling rule should not be separated from the corresponding output. If the buyer changes motif size for only one age band, the next version must record that exception clearly. Otherwise a correct render can still lead to incorrect manufacture.

3.1.2 Complementary Technical Concepts

The study draws on virtual fit evaluation, size grading, graphical placement control, version management and information handoff. Size grading changes garment dimensions according to a prescribed size rule. Artwork scaling can follow an additional buyer-defined size matrix and is not necessarily proportional to every pattern dimension. Version management records successive buyer comments and decisions. Output validation compares digital targets with a physical plot or scanned template under consistent units and coordinate references.

Template grading requires distinguishing garment sizes from motif-size rules. The shape of a sleeve or trouser leg may change continuously from one garment size to the next, while an embroidery flower could remain at the same percentage within an assigned age band. The anchor point is a separate property: a buyer may request that a motif be aligned to the hem across sizes rather than copied at a fixed distance from the waist. Therefore motif size and motif placement should be evaluated independently.

Micro-automation is analyzed through a task-level efficiency perspective. Its components include action frequency, time per manual interaction, error recovery and maintenance of scripts. For repeated operations, an apparent five-second saving may have practical value, but the net effect must account for execution failures, OCR mistakes and changes to the software interface.

3.1.3 Integration of Concepts

Together, these concepts suggest that success should be judged at the level of the complete workflow: whether the right garment appearance is communicated, whether size-specific placement instructions are unambiguous, whether buyer changes are recorded, and whether the receiving department can reproduce the approved design. The framework explicitly includes feedback cycles rather than treating approval as a single event.

The unified framework contains three linked output pathways: (A) template placement for multiple sizes, (B) virtual fit and design review, and (C) rendering and user-efficiency support. All begin with correctly identified inputs and end in a buyer- or production-facing deliverable. Revision tracking is common to all three. They differ mainly in what constitutes successful output: artwork location, design interpretation, or speed and repeatability of execution.

3.2 Conceptual Framework

Figure 3.1 conceptual framework (expanded into three linked pathways below):

Track A: base-size and graded patterns -> CLO3D motif placement -> buyer review -> approved plotting -> embellishment production.

Track B: DXF pattern and matched avatar -> CLO3D simulation -> buyer virtual comments -> revision -> physical sample and verification.

Track C: material calibration, surface details, saved presets and AutoHotkey micro-automation support the other two tracks. All tracks require scale checks and revision control.




Figure 3.1: Three-track conceptual framework developed from the author's reported practice.

3.3 Evaluation Questions and Indicators

Table 3.1: Conceptual dimensions and proposed evaluation criteria

Dimension	Operational definition	Possible evidence
Iteration	Number and nature of buyer comment cycles	Dated workbooks; version folder history
Artwork consistency	Whether motif size and position follow approved size rules	Placement tables; overlays; ruler measurements
Handoff complexity	Number of manual transfer operations between approval and embellishment production	Process observation; department checklist
Development time	Elapsed time and/or active labor time per verified workflow step	Timestamped task logs
Fit review	Documented visual design/fit comments before physical sampling	Buyer comments; annotated renders

Chapter 4: Research Methodology

4.1 Research Design

This dissertation uses an exploratory, descriptive, practice-based case-study approach. The researcher is also a practitioner responsible for 3D apparel development in the observed setting. The approach is appropriate for documenting process stages, identifying operational constraints and generating practical improvement recommendations. It does not, without further validation, establish an objective numerical effect of CLO3D on cost, lead time or material use.

The primary method is reflective practitioner inquiry supported by descriptive case mapping. This design is appropriate because the researcher directly participates in the processes examined and has experience of how the files, comments and outputs travel between departments. Its purpose is to establish a clear and reproducible account of professional practice and identify questions for later comparative testing. It is not a randomized experiment, a representative industry survey or a controlled before-and-after measurement.

The unit of analysis is a development workflow for a style, rather than an individual employee. Each workflow is defined by its input, procedure, approval event and output. A style may pass through several versions; the existence of revision rounds is described, but exact counts are not asserted without supporting workbooks or version histories.

4.2 Case Selection and Scope

Two cases are purposefully selected because they illustrate different outputs of the same software environment. Case A is a childrenswear template workflow involving multiple age sizes and embellishments such as embroidery, print and crochet. Case B is a buyer-led virtual prototyping workflow in which 2D CAD patterns are simulated on a specified digital avatar and revised before a physical sample request. The cases are discussed as professional experiences within an apparel manufacturing organization, rather than as a random sample of the Bangladesh garment industry.

The selection is purposive rather than statistically representative. The childrenswear case has a distinctive multi-size and multi-motif challenge. The virtual denim case illustrates fit, wash and detail review before a physical sample. A supporting third line of observation considers texture creation, saved technical presets and AutoHotkey scripts. Taken together, the cases capture different uses of 3D technology within a single professional environment.

The time frame is retrospective professional experience since the author joined Al-Muslim Group in August 2025. The researcher’s account reflects normal responsibilities and may

blend repeated experiences from more than one style. Where a particular observation cannot be tied to a named, non-confidential file, it is marked as a general practice description rather than an individual verified result.

4.3 Data Collection

Potential primary evidence includes a researcher process log, original CLO3D screenshots, non-confidential pattern dimensions, dated buyer comment excerpts, revision version history, approval records, workflow diagrams and any approved physical-template comparison photographs. Secondary evidence includes scholarly publications on virtual garment fitting, digital sampling and technical software documentation. The author must verify the availability and permission status of every item before presenting it as collected data.

Evidence is organized into three classes. Class 1 comprises the researcher's first-hand description of activities and bottlenecks; it supports a process narrative but cannot alone establish numerical performance. Class 2 would comprise artifacts such as dated screenshots, CAD files, approval versions and physical plot photographs; these could corroborate specific cases if approved for academic disclosure. Class 3 comprises external publications and vendor documentation; these support technical concepts and claims about available software features.

Because the dissertation is prepared under a short academic deadline, no new questionnaire or fabricated survey dataset is included. The reference dissertation's statistical approach is not copied. Any future sample timings, production defects or savings percentages will require a separate, systematically collected dataset.

4.4 Research Instruments and Software

The central software is CLO3D, supported in practice by industrial 2D pattern CAD, Adobe Illustrator, Photoshop and digital material authoring tools where relevant. Process measurements can be documented in a spreadsheet using columns for style code (anonymized), reference size, number of graded sizes, artwork type, motif scale, placement coordinates, comment round, time spent, output method and result. No unsupported assumptions are made about a plotter's ability to preserve graphics across file conversions.

Application environment: CLO3D for 2D/3D garment construction, virtual sewing, simulation, graphics and render preparation; industrial CAD/DXF for pattern source information; Adobe Illustrator for path and vector editing; Photoshop for garment washes and visual preparation; Substance 3D Painter for layered material effects when required; Inkscape for SVG processing and HPGL output; and AutoHotkey for local user-interface automation. Plotter software is described generically as compatible marker/plot-output software because

machine model and workflow settings have not been independently verified in this manuscript.

The author also has experience with Marvelous Designer, which shares many garment simulation concepts with CLO3D. The case analysis itself focuses on CLO3D, because that is the primary commercial workflow described. No claim is made that all features are identical across products or versions.

4.5 Quality Control and Validation

Case descriptions are to be checked against available non-confidential artifacts, for example a reference sample and a final approved template. If digital-to-physical artwork transfer is evaluated, a trial print should include a known-length scale line and reference coordinates so that the final plotted distance can be measured with a ruler. Scale error may be reported as (measured length − target length) / target length × 100, with the absolute error also recorded in millimeters. These calculations are proposed tests, not results already obtained.

Plotting validation should use an independently measured test line and motif bounding box. For a 100 mm control line, for example, the observed difference equals measured plotted length minus 100 mm; absolute error is the magnitude of that difference. The same procedure should be performed along horizontal and vertical directions because image and device scaling can differ by axis. A screenshot alone is not proof of dimensional fidelity.

Virtual fit validation should compare a defined body measurement set, garment measurement set, fabric input file and camera view. Where actual fabric testing is unavailable, material inputs must be identified as approximations. The comparison should separate visible design decisions from claims about physical fit accuracy.

AutoHotkey scripts are subject to stability testing. Pixel-color detection can fail when display scale, theme or highlight colors change; OCR can select an incorrect menu item. A test record should therefore include task success rate, user recovery steps and software version. These checks limit the risk of trading manual delays for hidden automation errors.

4.6 Analysis Techniques

The data will be organized through process mapping, descriptive comparison, comment categorization and evidence tables. Any actual numerical records can be summarized using counts, medians or averages as appropriate, but the study will not invent respondent numbers, p-values, time savings or reduction percentages. Qualitative evidence will be used to distinguish observed constraints, buyer-driven changes and potential improvements. Statistical hypothesis testing is not required for this small case-study design.

Thematic coding groups work observations into (1) design and visual communication, (2) dimensional placement, (3) approval and revision management, (4) digital/physical transfer, and (5) operator-time optimization. For an eventual numerical study, time per completed style, number of revisions, plot accuracy and physical sample count are the preferred descriptive measures. Correlation and hypothesis tests are not attempted without an appropriate dataset.

For a future measured comparison, percentage reduction would be computed as (baseline time minus improved time) divided by baseline time, multiplied by 100. Such a formula is provided as a method only; this dissertation contains no actual measured baseline and therefore reports no calculated reduction.

4.7 Ethical Considerations

Customer specifications, personal information, proprietary artwork, production files and commercial correspondence may be confidential. Written organizational authorization should be obtained for any identifiable company, buyer, style or artwork evidence that will appear in the dissertation. Without authorization, the draft should use Buyer A and Buyer B and replace artwork with author-created demonstrator examples. Workbooks, screenshots and files should be redacted as necessary, and all quoted comments should be reproduced only when permitted.

Buyer identifiers are included only as professional context reported by the author. Before any public upload, written approval should be obtained for reproducing logos, motif artwork, proprietary grading instructions, physical samples or internal email/workbook excerpts. Otherwise the corresponding material should remain anonymized, and any proprietary dimensions should be replaced with a separately created academic demonstrator.

4.8 Expected Findings

The case-study design is expected to describe two operational roles of CLO3D, clarify repetitive approval loops, document manual steps still needed after digital approval and identify potential criteria for improved information transfer. These are expectations, not reported outcomes. Conclusions will be restricted to what the examples and verifiable records support.

4.9 Limitations

The cases depend on one practitioner’s experience and may be influenced by differences in product types, buyer requirements, team capability and legacy software. The research does not include a controlled trial or representative factory survey. Unless independently tested, a

suggested direct-output workflow cannot be presented as technically successful. Confidentiality constraints may also limit which production illustrations can be published.

A central limitation is that the researcher reports a working digital plotting route and perceived time savings without a calibrated time-and-motion trial. In addition, motif-size bands can vary with buyer comments, and the draft bands are not claimed as final specifications for any particular style. The study is analytical and descriptive, not a quantitative test of productivity superiority.

Chapter 5: Data Presentation and Analysis

This chapter presents a structured qualitative account of the practitioner-reported workflows. Performance estimates and future measurements are identified separately from verified empirical records. The analysis concerns process sequence, source information, feedback interpretation and the reliability of the digital-to-physical handoff.

5.1 Case A: Childrenswear Graded Embellishment Templates

The first case draws on the author's reported work for the Next Girls Department and concerns girls' clothing within a size range described as 3 to 16 years. One base-size sample, generally size 6, acts as the visual reference for the style. Digital pattern grading allows the same garment to be inspected at other sizes, and embellishment positions are adapted according to both garment proportions and buyer-specific artwork scales. The researcher described using CLO3D internal lines and graphics to produce viewable placement templates, then sharing size-based screenshots and dimensional instructions for review.

An important distinction is that a garment grade rule and an artwork grade rule may be separate. A motif might be kept at 100% for one size band while the garment itself continues to increase in size. Therefore, placing the motif by an unchanged proportional offset can change its apparent position across sizes. Templates are reviewed for perceived balance as well as measurement compliance, and buyer comments may override the initial scale matrix.

The author receives a physical reference garment or corresponding technical information and recreates the embroidery/print/crochet look on a size-6 digital pattern. Internal lines are used as reference geometry; graphics are placed on the pattern and visually compared with the sample. Motif dimensions and anchor positions are prepared for other sizes, and a separate screenshot or view is produced for technical review of each graded pattern.

The task becomes particularly demanding where a style includes several motifs with different orientations and relationships to seams. Moving a flower closer to the hem, for example, should not cause inconsistent spacing between neighboring motifs. If the buyer prefers the size and proportions of the black-seal reference rather than an earlier template, the artwork scale and placement must be reconsidered together.

The number of sizes from 3Y to 16Y inclusive is fourteen. Each size is its own pattern output, even where a group shares the same artwork scale. This distinction matters because equal-size motifs can require different coordinates and surrounding spacing on differently graded pattern pieces.

5.2 Provisional Artwork Scale Matrix

Table 5.1: Initial artwork scale bands for the working example

Size band	Initial motif scale	Verification status
3–5 years	80%	Working rule; confirm for chosen style
6–9 years	100%	Working rule; size 6 is typical reference
10–13 years	120%	Working rule; buyer may override
14–16 years	140%	Working rule; buyer may override

The size bands above are provisional and should be checked against the actual workbook for the case selected. Sizes 3 through 16 inclusive provide 14 nominal age-size labels: one reference size and 13 other sizes, if all labels are used. The spoken account contained some overlapping size-band references; the final dissertation must use the verified rule for the actual style.

The scale matrix represents the author's stated initial working rule, not a fixed industry standard. The 6Y reference typically starts at 100%. The dissertation uses the proposed 3–5Y / 6–9Y / 10–13Y / 14–16Y grouping as a working example, subject to verification against the approved buyer workbook for the style. A buyer's revised comment can override any initial scale percentage. Every override should be documented with its effective size band and version.

5.3 Template Approval Sequence

The researcher's description indicates an initial template prepared by the 3D department and shared with the buyer's Bangladesh-based technical team. The local garment technologist checks basic alignment and acceptability and, if suitable, forwards the material for international buyer review. Buyer comments are then returned in a spreadsheet-based workbook. The designer revises motif proportion, arrangement or placement and resubmits as required. This feedback cycle may repeat until formal approval. The word "approved" should refer to an actual documented buyer decision rather than a visual assumption by the author.

Once the initial template is made in CLO3D, it is transmitted to the buyer's Bangladesh technical office in Uttara. A garment technologist checks whether the template looks proportionate and is technically acceptable for forward review. The United Kingdom team then examines the placement, comparative appearance across sizes and relationships between

motifs and construction features. Comments are returned in an Excel workbook; the 3D department revises the relevant sizes and resubmits. This continues until approval.

This is a quality-control loop, not a one-time handoff. The workbook should indicate whether a comment concerns the reference motif size, a new percentage, hem stacking, the spacing of multiple motifs or another issue. Without one authoritative comment history, a technical team can mistakenly mix instructions from different revisions. The author's departmental role includes interpreting these comments and coordinating changes across the graded templates.

5.4 Digital-to-Physical Handoff

After template approval, the industrial CAD pattern is prepared for plotting. According to the described process, digital artwork and location information are not transferred in a directly usable form through the existing pattern-output workflow. Instead, the artwork is printed separately, cut out and attached manually to a full-size paper pattern, using the provided dimensions as a reference. The resulting template is passed to the relevant embroidery or print unit, which scans or reinterprets the information for its machinery. The exact intermediate steps can differ among production departments. This is a key focus of the proposed improvement investigation.

The former manual hard-copy route required a pattern master to print the garment pattern, print the separately supplied motif design, cut the artwork, attach it to the intended location by measuring from a reference, and distribute the result to departments such as embroidery or print. A receiving department might rescan the printed layout. Each transfer involved additional labor and opportunities for misalignment, repeated handling or incorrect size interpretation.

The author tested and then adopted a digital transfer route: (1) finalize the graded template in CLO3D; (2) export the required pattern arrangement as PDF; (3) open the PDF in Adobe Illustrator; (4) preserve or convert artwork paths and save as SVG; (5) open the SVG in Inkscape; (6) export as HPGL; and (7) load the HPGL file in compatible marker/plotter software for hard-copy plotting. In this route the intention is to print both the pattern geometry and motif positions in a common coordinate system, rather than recreate their alignment by hand.

According to the author's account, this method has been used successfully for direct motif placement on hard-copy patterns and has reduced perceived workload, hand placement errors and disagreement over dimensions. The statement is a practitioner observation: neither precise labor time nor absolute positional error has been independently measured for the present

dissertation. The route should therefore be presented with a test print, dimension control and file-conversion record before being generalized to every style and machine.

A practical safeguard is to include a 100 mm horizontal and vertical check line, a reference rectangle around the artwork, unit labels and a clear version identifier. Before printing a 14-size pack, a single control file should be plotted and measured. Particular attention must be paid to whether raster graphic objects survive vector conversion; any lost graphic, altered stroke or missing motif invalidates the output even when pattern outlines appear correct.



Figure 5.1: Practitioner-described digital artwork-to-plotter conversion and validation pathway.

5.5 Case B: Buyer-Led Virtual Prototyping

The second case draws on virtual sample development described by the author for H&M, before a physical sample is requested. A buyer-supplied pattern is received in DXF and imported into CLO3D. The designer constructs the garment on a virtual avatar intended to match the dimensions of the buyer's physical fitting form. A rendered sample is reviewed by the buyer and comments may address visible design proportions such as pocket size or placement, or the silhouette of a garment such as a baggy jean. When a comment requires a construction or fit change, the pattern and garment must be adjusted and simulated again. The physical sample follows the approved digital stage according to the buyer's process.

The use of dimensionally matched avatars provides a clear point of reference, but it does not prove that the simulation predicts every aspect of physical fit. Actual fabric characteristics, avatar posture and the accuracy of pattern modifications remain relevant limitations, consistent with virtual fit research (Lee & Park, 2017).

For denim trousers, the author imports a buyer-provided DXF pattern, assembles the panels in CLO3D and simulates them on a digital avatar corresponding in measurements to the buyer's physical mannequin. A first render is sent for review. The buyer may request a larger pocket, a different pocket shape, a baggier silhouette, or amendments to fit and pattern geometry. The corrected garment is rendered again, allowing successive design decisions before a physical sample is commissioned.

The digital stage changes the sequence of decision-making. Instead of discovering every visual or pattern problem after sewing and shipping a sample, the team can address at least some issues in advance. It does not follow that every physical cycle is removed. Denim wash chemistry, abrasion, shrinkage and production sewing may alter the garment and still require real inspection.

The described practice demonstrates a buyer-led process for pre-physical review, but this manuscript does not include dated H&M approval records. Consequently it reports no verified reduction in shipping cost, number of samples or calendar lead time. Those remain plausible but unmeasured outcomes for future research.



Figure 5.2: 3D-assisted digital review process before physical garment sampling.

5.6 Comparative Workflow and Evidence Status

Table 5.2: Comparison of described workflow stages and evidence status

Area	**Observed/described workflow**	**Information needed for measurable analysis**
Buyer review	Digital images and comment workbooks	Number of comment rounds per documented style

Pattern source	Industrial CAD/DXF patterns	File format, scale and version record
Graded motif placement	CLO3D internal lines and graphics	Reference dimensions and final approved matrix
Manual template output	Print, cut, attach and scan	Task timing, material use and measured alignment
Virtual sample	Digital prototype before physical sample	Dates of virtual approval and physical sampling
Potential direct transfer	Researcher explored possible alternatives	File-format test with measured plot output

The following tables differentiate directly described process steps from measurable outcomes that remain undocumented. For example, “direct plotting is used” is supported by the researcher’s account; “direct plotting saves 72% time” would require a timed baseline and is not stated. The distinction preserves the credibility of the case study.

5.7 Revision and Comparison Log

Table 5.3: Illustrative buyer-comment and revision log (unfilled template)

Anonymized case	**Version/date**	**Buyer change**	**CLO3D or CAD action**	**Verification**
A: girlswear	[V1/date]	[Motif scale or placement comment]	[Action]	[Approval or next comment]
A: girlswear	[V2/date]	[Comment]	[Action]	[Approval or next comment]
B: jeans	[V1/date]	[Pocket or silhouette comment]	[Action]	[Approval or next comment]

For both cases, version labels should distinguish a preliminary sample, buyer comments and the approved version. The case log is an example template only; it intentionally contains no fabricated buyer comments, dates or approval signatures. If confidential correspondence cannot be reproduced, the author may provide a short anonymized paraphrase or remove the row while retaining the process description.

5.8 Analysis of Technical Constraints

Both cases reveal that the image viewed by a buyer and the information required by production are not always the same kind of artifact. A rendered garment is effective for visual

review, but the physical production team may require pattern geometry, graded annotation, full-scale placement coordinates or separate embroidery artwork. Exporting a visual snapshot is not equivalent to exporting a production-ready pattern file. In a proposed improvement trial, output accuracy would be demonstrated only when a plotted result matches the approved intended scale and placement. Technical feasibility must also be assessed for the specific software versions and printer or plotter pipeline installed at the factory.

5.9 Case C: Denim Wash Visualization and Digital Material Realism

Because the factory develops denim-oriented products, simulated wash appearance is a substantial part of buyer communication. The author commonly prepares wash textures in Adobe Photoshop, placing faded, darkened, whiskered or worn areas in relation to the garment's shape. The resulting texture is applied to the virtual jeans through CLO3D material or graphics controls. Render quality then depends on appropriate lighting, fabric response and other details such as zipper construction, seam puckering, topstitching and pocket stitching.

Additional layered surface effects may be prepared with Substance 3D Painter. The author reports that this is useful where a single CLO puckering treatment is visually insufficient and multiple localized material effects are needed along one seam. In interpreting this practice, a surface map must be distinguished from simulated cloth mechanics. Layering normal or height effects can increase apparent depth and realism but does not independently validate the actual mechanical deformation of a sewn or washed garment.

An appropriate academic comparison would show the same simulated jeans (a) with a basic material, (b) with Photoshop wash mapping, and (c) with the final seam and surface detailing, while keeping the garment, avatar, pose and camera constant. No unsupported buyer preference score is supplied in this study; the author describes positive buyer feedback in general terms.

5.10 Workflow Micro-Automation Using AutoHotkey

The author has written AutoHotkey routines to speed up recurring actions within CLO3D. A reported example concerns a "Match Up" command used when examining corresponding pattern points and curve continuity. Where a convenient native shortcut was unavailable in the author's interface, the script identifies selected yellow points by pixel color, moves the cursor and opens a context menu. It then uses OCR within a defined screen region to locate and click the required menu command. This is a user-interface automation rather than a native CLO API integration.

A second script enters frequently used collision-thickness and render-thickness values after the relevant objects are selected. The author prefers particular settings for certain tasks, and the automation reduces repeated manual input. He also saves reusable visual settings and puckering effects to apply across future styles. These practices illustrate the value of repeatability for a department that prepares several garment developments per day.

The author self-reports typical personal output of approximately three to four 3D garment tasks a day, with up to five under favorable conditions. This is a context statement, not a controlled productivity benchmark: “3D garment” tasks differ in pattern complexity, wash development, buyer revisions and render requirements. No head-to-head comparison with other designers is attempted.

Automation has risks. Pixel colors can change, OCR can misread menu labels, screen resolution can shift and selecting the wrong menu command can damage a file. For production use, scripts should check that CLO3D is active, confirm target selection, limit searches to intended windows, stop safely on uncertainty and provide a clear manual fallback. A reliable automation is one that saves operator time without making silent errors.

5.11 Practical Performance Indicators

The future quantitative evaluation should include four primary indicators: active labor minutes to prepare an approved template, absolute motif-placement error (mm) on a plotted output, total number of design review iterations before physical sampling and number of physical samples made per comparable style. These variables should be measured across repeated styles with similar complexity. Comparisons should identify the artwork count, number of sizes, fabric category and buyer comment complexity.

A fifth indicator is operational reliability: the percentage of plotted or automated tasks completed correctly without manual recovery. A method that is very fast when it works but frequently loses artwork or selects the wrong OCR result may not provide a net benefit. This dissertation recommends an audit trail rather than offering a numerical result unsupported by a baseline.

Table 5.4: Proposed performance indicators and evidence limitations

Indicator	Proposed measurement	Status in this study
Manual template effort	Observed person-minutes for one 14-size style	Author estimates about one working day; not timed
Digital plot effort	Person-minutes from PDF export to printed output	Reported faster; no timed dataset

Motif accuracy	Maximum absolute error in mm at reference anchors	No calibrated measurement provided
Virtual sampling	Number of iterations before / after first physical sample	Workflow observed; no complete count
3D production	Completed styles per person-day, with complexity category	Author reports 3–4 typical and up to 5; not benchmarked
Script reliability	Successful executions divided by attempted executions	Not measured

5.12 Synthesis and Evidence Boundaries

The case analysis indicates three distinct modes of value. First, CLO3D can support visual design decisions before physical sample construction. Second, graded placement made in a digital pattern environment can support more consistent communication of artwork location. Third, converting digital development output into plotter-compatible geometry and automating small interface operations can simplify repetitive work. These are supported as practitioner-described capabilities, not as statistically demonstrated cost savings.

The strongest original contribution is the digital-to-physical transfer method because it directly addresses a production bottleneck after buyer approval. Yet it is also the area where technical verification is most important: an HPGL plot may look correct at a glance while carrying scale, position or missing-object errors. The recommended academic extension is a documented comparison using one simple motif style and one complex multi-motif style across the full size set.

Chapter 6: Findings and Practical Design Development

6.1 Preliminary Findings of the Case Analysis

6.1.1 Two Practical Roles of CLO3D

The practitioner account identifies two different applications: garment visualization for buyer fit/design discussion and size-graded template preparation for embellishment placement. The latter is an operationally important design-communication task and should not be treated as a secondary or unrelated function. A complete evaluation of 3D practice should include both kinds of output.

6.1.2 Buyer Comments Drive Iterative Development

In both cases, digital outputs are reviewed by others and changed in response to comments. The purpose of the review varies: a children's template may be rejected because motif size, balance or hem placement looks wrong at a particular age size, while a virtual jean may be rejected because the pocket scale or overall silhouette is inconsistent with the brief. The same CLO3D environment supports repeated visual interpretation but does not remove the need for human technical judgment.

6.1.3 Manual Handoffs Remain Important

The described plotter and embellishment preparation method includes manual artwork cutting and attachment after digital approval. This establishes an observable process step that could be targeted for improvement. However, the dissertation cannot state that direct printing is faster, cheaper or more accurate until a tested method demonstrates the result. The next research step is to document a baseline process and verify a controlled output experiment.

6.1.4 Fit Realism Has Practical Limits

A digital avatar matched in body dimensions to a physical mannequin allows a more relevant visual reference than an arbitrary avatar. Nevertheless, simulation remains an approximation and the buyer's decision to authorize a physical sample is not evidence that virtual and physical fit are identical. The study should record visible fit observations separately from measurements and physical fitting results.

6.1.5 Direct Plotting Addresses a Post-Approval Bottleneck

The reported PDF–Illustrator–SVG–Inkscape–HPGL route addresses the previously manual effort of reproducing buyer-approved motifs on printed patterns. The conceptual improvement is preservation of a single digital reference for pattern shape and motif position. The author

reports successful practical use of the method. The study cannot quantify gains or independently certify tolerance without paired test prints and dimensional measurements.

6.1.6 Detailed Denim Rendering Supports Visual Communication

Photoshop wash graphics, appropriate fabric behavior, visible topstitching, zipper details and seam puckering help communicate realistic denim product concepts. Substance 3D Painter may add layered surface detail when necessary. However, surface realism must not be equated with verified physical properties, and the final washed production garment remains the reference for actual finish and hand-feel.

6.1.7 Reusable Assets and Micro-Automation Support Repetitive Work

Automated menu selection, repeated property entry and saved detail settings are practical examples of operator-led optimization. Small individual savings may accumulate when an action is repeated frequently. The study documents the mechanisms and the author's perception of benefit, while recommending runtime logging and error checks before expressing productivity improvements as measurable results.

6.1.8 An Integrated Digital Workflow Is Not Yet a Sample-Free Workflow

The prospective model is digital-first rather than digital-only. Before sewing, the team may resolve visible design issues and some fit questions through simulation. A physical sample remains essential for specified wash, seam performance, mechanical comfort, shrinkage, manufacturability and buyer-specific validation. This distinction forms the basis of a realistic roadmap for future use.

6.2 Design Translation and Original Demonstrator Development

Following the applied-design section used in the reference dissertation, this chapter outlines an academic demonstrator assembled from three kinds of deliverable: an annotated graded-placement template, a controlled vector-to-plot output, and a digital denim sample with visible material details. The demonstrator is specified conceptually; the dissertation does not falsely claim to include photographs of commercial buyer styles or to have completed a new controlled experiment. Workplace screenshots should only be inserted if disclosure permission is available.

6.2.1 Design Concept

Working concept: "Digital to Production from Virtual Approval to Accurate Garment Communication." The concept follows the same design as it moves through two-dimensional pattern geometry, three-dimensional interpretation, buyer feedback, and preparation for

physical production. The visual narrative emphasizes process accuracy, repeatable communication and the relationship between commercial appearance and manufacturing instructions.

6.2.2 Material and Surface Development

The digital materials can be documented through fabric type, weight, thickness, visual texture and any surface maps used. If a normal map or height map is employed to improve surface appearance, its role should be described precisely and compared visually with an image of the intended material. The design presentation should avoid treating a rendered textile as physically validated merely because it looks realistic.

For an original academic demonstrator, a student-created five-pocket jeans design may be used with non-confidential 2D patterns. The sample should show dark-to-vintage wash options created through color mapping, topstitching and selected seam details. Its simulated fabric should identify whether measurements were actually captured or whether a preset was used. A second, simplified childrenswear panel can contain three original floral shapes with size-dependent scale rules to illustrate motif scaling separately from placement.

A useful documentation panel would list color/texture inputs independently from the simulated physical-property inputs. Example labels are: pattern source and version, digital fabric type, base texture file, normal/height treatment, target camera view, file date and output resolution. No specific Pantone code or unmeasured fabric-stiffness value is invented.

6.2.3 Garment Lineup and Technical Specifications

Table 6.1: Original demonstrator lineup and technical evidence requirements

Original look	**Design focus**	**Required visuals / evidence**
Look 1	Base-size to graded-size motif placement	2D pattern, artwork scale matrix, approved placement views
Look 2	Coordination of embroidery/print/crochet placement	Motif placement map and production handoff diagram
Look 3	Virtual fit and buyer-led design changes	Front/back 3D views, annotated fit issue, revised view

6.2.4 Virtual Fit and Final Render Presentation

Original screenshot comparisons should use a consistent camera angle, lighting, pose and garment scale, with clear permission and source captions. Where commercial images cannot be disclosed, the original process diagrams illustrate the workflow without implying that a new experiment was performed.

Chapter 7: Recommendations and Conclusions

7.1 Recommendations

First, distinguish buyer-facing visualization files from production-facing placement specifications. Every placement deliverable should identify the pattern version, reference size, motif version, motif scale, units, anchor points and approved revision state. Second, retain versioned comment histories so that scaling and placement corrections can be traced to the correct buyer instruction. Third, verify the output pipeline with a controlled test pattern before assuming that graphics, internal lines and scale will survive transfers between CLO3D, a pattern CAD system and the plotter. Fourth, train cross-functional teams to interpret both visual renders and dimensional template instructions; neither format should be treated as a complete substitute for the other. Fifth, evaluate any proposed process improvement against a measured baseline using the same style, size and artwork complexity.

Further research can expand the present descriptive account into a multi-style comparative study. Useful indicators include time per revision, number of approval cycles, absolute placement error in millimeters, full-scale artwork distortion, physical sample count and department handoff counts. A repeatable digital transfer method would require specific software-version checks and agreement from the CAD and production teams. It should not be deployed for commercial production without dimensional and content validation.

For graded embellishment templates, a short standard operating procedure should require a locked reference sample, per-size scaling worksheet, fixed placement anchors, reviewer identity, approval version and measured plot calibration. The instruction “keep the motif appearance proportionate” should be translated into concrete measures for example, an agreed motif bounding rectangle and distance to hem rather than relying solely on an image.

For denim virtual samples, a standard package should contain the approved pattern version, DXF unit system, avatar measurement chart, calibrated or declared fabric preset, a minimum set of agreed camera angles and a list of changed details. Any simulated wash should be labeled a visual proposal until physical finishing verifies color and treatment. The buyer’s physical mannequin remains an independent verification tool.

For scripting and team training, store AutoHotkey scripts in controlled versions with a short user guide, test against the current CLO3D build, and include an emergency stop. Shared libraries of stitch, zipper, puckering and wash presets can promote consistent departmental output. These improvements should be judged by error-free completion and controlled turnaround time rather than by render volume alone.

For academic follow-up, collect at least several comparable styles using a consistent stopwatch, number of motifs and size count. Compare manual and digital approaches on identical geometry, note any rejected or failed plots, and calculate the amount of error and time required. A separate virtual-to-physical fit study should use actual fabric swatches and defined garment measurements. These studies would turn the present professional case record into evidence for quantified improvement.

7.2 Conclusion

This dissertation documents 3D fashion technology as more than a presentation method. In the author's practice at Al-Muslim Group, CLO3D supports both virtual garments for buyer-led design review and size-graded templates communicating embroidery, print and crochet placement. Digital denim materials, surface details and user-interface automation support this work. The reported PDF–Illustrator–SVG–Inkscape–HPGL plotting route addresses an important production handoff after digital approval. Together, the cases show interactions across CAD, merchandising, technical review, sample making and embellishment production. The contribution is a transparent practice-based workflow analysis, not statistically validated savings. 3D-centered product development may improve continuity when file transfers, fabric inputs, buyer comments and physical checks are controlled; further studies should measure actual efficiency and sampling outcomes.

References

Baria, B., Shahid, M. A., Misra, A., Hoque, M. B., Rahman, M. M., Hossain, M. D., & Das, D. (2026). Transformative effect of 3D sampling technology for the ready-made garment industry: A review. Textile Research Journal, 96(15–16), 1719–1741. https://doi.org/10.1177/00405175251360399

Lee, E., & Park, H. (2017). 3D Virtual fit simulation technology: Strengths and areas of improvement for increased industry adoption. International Journal of Fashion Design, Technology and Education, 10(1), 59–70. https://doi.org/10.1080/17543266.2016.1194483

Papachristou, E., Kalaitzi, D., & Pissas, V. (2023). A methodological framework for the integration of 3D virtual prototyping into the design development of laser-cut garments. Journal of Engineered Fibers and Fabrics. https://doi.org/10.1177/15589250231194621

Porterfield, A., & Lamar, T. A. M. (2017). Examining the effectiveness of virtual fitting with 3D garment simulation. International Journal of Fashion Design, Technology and Education, 10(3), 320–330. https://doi.org/10.1080/17543266.2016.1250290

Zangue, F., Pirch, C., Klepser, A., & Morlock, S. (2020). Virtual fit vs. physical fit: How well does 3D simulation represent the physical reality? Proceedings of 3DBODY.TECH 2020. https://doi.org/10.15221/20.21

CLO Virtual Fashion. (n.d.-a). 2D Pattern (DXF) Import/Export. CLO Support. https://support.clo3d.com/hc/en-us/articles/115000493067-2D-Pattern-DXF-Import-Export

CLO Virtual Fashion. (n.d.-b). 2D Pattern (AI/PDF) Import/Export. CLO Support. https://support.clo3d.com/hc/en-us/articles/115004273427-2D-Pattern-AI-PDF-Import-Export

CLO Virtual Fashion. (n.d.-c). Fabric Kit Manual. CLO Support. https://support.clo3d.com/hc/en-us/articles/360041074334-Fabric-Kit-Manual

Inkscape Project. (n.d.). HPGL output extension (hpgl_output.py), software documentation. https://inkscape.gitlab.io/inkscape/doxygen-extensions/hpgl__output_8py_source.html